

## 3/4 HP (.56 kw)

Incorporating 9 different models offering pressures up to 15,000 psi (1034 bar) and flow rates up to 2.4 GPM (9.0 L/min), this series of pumps takes full advantage of Haskel's many years of proven design basics.

This series operates with maximum air drive pressures up to 100 psi (7 bar) and utilises a bottom liquid inlet port as standard. A noise reduction modification is available for applications where noise level is an important criteria. Mufflers are standard on all pumps.



### ✓Key Features

- Pressures to 15,000 psi
- Flow rates to 2-4 GPM (9.0 L/min)
- 9 models
- Hydraulic fluids: petroleum base, HWCF & 95/5, plain water, liquefied gases

### ✓Model

Model	Ratio Dash No.	Actual Area Ratio	Max rated output pressure				Displacement per Cycle	
			Continuous		Intermittent		Cu. In.	CC
			psi	bar	psi	bar		
4B	- 14	18.0	1500	103	1500	103	0.900	14.7
4B	- 21	24.0	2300	159	2300	159	0.600	9.8
4B	- 25	29.0	2700	186	2700	186	0.500	8.2
4B	- 30	34.0	3200	221	3200	221	0.430	7.0
4B	- 37	42.0	3800	262	3800	262	0.350	5.7
4B	- 55	63.0	6000	414	6000	414	0.220	3.6
4B	- 75	86.0	7800	538	7800	538	0.170	2.8
4B	- 100	114.0	10600	731	10600	731	0.130	2.1
4B	- 150	171.0	15000	1034	15000	1034	0.088	1.4

✚Optional modification available upon request