

6 HP (4.5 kw)

Incorporating 20 models, this heavy duty range of double acting pumps provide pressures up to 10,000 psi (700 bar) and flow rates up to 23 GPM (87 L/min.).



This pump is designed to operate with air drive pressures between 40 to 130 psi (2.8 and 9 bar). For drive pressures 3-40 psi order 51875-1 mod.

Mufflers are standard on all pumps.

✓Key Features

- Pressures to 10,000 psi
- Flow rates to 15 GPM (56 L/min)
- 20 models
- All hydraulic fluids, water-plain or DI, solvents

✓Model

Model	Ratio Dash No.	Actual Area Ratio	Max rated output pressure				Displacement per Cycle	
			Continuous		Intermittent		Cu. In.	CC
			psi	bar	psi	bar		
GWD, GSFD, DGFD	- 12	14.8	8000	552	10000	690	15.900	280.6
DGSFD, DGSTVD	- 12	14.8	8000	552	10000	690	15.900	280.6
GW, DGF, GSF	- 35	40.3	4375	302	4375	302	6.000	98.3
DGSF, DGSTV	- 35	40.3	4375	302	4375	302	6.000	98.3
GW, DGF, GSF	- 60	69.0	7500	517	7500	517	3.500	57.4
DGSF, DGSTV	- 60	69.0	7500	517	7500	517	3.500	57.4
GW, DGF, GSF	- 100	115.0	8000	552	10000	690	2.100	34.4
DGSF, DGSTV	- 100	115.0	8000	552	10000	690	2.100	34.4

✚Optional modification available upon request